

DigiPoS DS800

Thermal Receipt Printer

New to the DigiPoS range, the DS800 is a very small footprint thermal receipt printer that is packed with features.

Available in black and white, the DS800 compliments any retail or hospitality environment. The DS800 offers fast text (150 mm per second), high resolution graphics and barcodes, as well as easy-to-use features such as drop-in paper load and auto-cutter.



- Fast 150mm/sec Print Speed
- ESC/POS Compatible
- Easy paper loading
- 3 year warranty



DigiPoS DS800

Thermal Receipt Printer

Specifications

Print Method	Thermal line printing
Print Font	Font: 9 x 24 (FontA) 12 x 24 (Font B) Column Capacity: 64 Columns (FontA) 56 Columns (Font B) Dot Density (DPI) 203 x 180 (Font A) 180 x 180 (Font B) Dot Pitch (mm) 0.125 x 0.141 (FontA) 0.141 x 0.141 (Font B) Effective Printing Width 72mm, 576 Dots (FontA) 72mm, 512 Dots (Font B) Character Set: 95 Alphanumeric 32 International 128x7 graphics Bar Code: EAN-8, EAN-13, CODE 39, CODE 93, CODE 128, ITF UPC-A, UPC-E, CODABAR, PDF 417 Paper Handling: Drop In, Auto Cutter, Near End Sensor
Interface Options	RS-232C Bi-directional parallel USB
Print Speed	150mm / sec (47 lps, 0.125" conversion) max.
Thermal Paper	Dimensions (mm): Width: 80mm ± 0.1 Roll Diameter: Maximum 83 Roll Core: 12.5mm ± 0.5 Thickness (mm): 0.06 to 0.09
Current consumption	Approx 1.5A (mean)
Power	24 VDC +/- 5% (Supplied via a DigiPoS 24V Power Supply Module)
Power Consumption	Approx. 38 W
D.K.D. Function	2 Drives
Overall Dimensions (mm)	152 (W) x 194 (D) x 148 (H)
Weight	Approx 1.6 Kg
Factory Options	N/A
Reliability MTBF	19 x 10 (4) hours
Reliability MCBF	60 x 10 (6) lines

