



# DigiPoS IT 1500

• 15" All-in-One Touch PoS System



*The DigiPoS Integrated Touch (IT) 1500* is the new innovative semi-integrated touch screen point-of-sale system with a stylish design, specifically for the retail, hospitality and leisure market.

It features advanced technology based on the similar ease and functionality of DigiPoS Retail Blade™ technology. This system features outstanding reliability and a simple design, allowing for secured, yet easy access to internal components. It utilizes Intel processing power for high-performance demands and can endure the knocks and spills of harsh operating environments.

While conserving valuable counter space, the 15.1" TFT LCD Panel Display offers wide angle adjustment for true visibility and with the added option of the 10.4" LCD display, retailers can enhance the customer experience providing in-store advertisements and special offers. Alternatively the Standard 2 line / 20 character Rear Customer display is available.

## ADVANTAGES

- o Secure, easily accessible internal HDD/CD-ROM (No tools required)
- o Easily integrated with a Customer Display or Secondary LCD Display
- o Two front accessible USB ports, two in rear
- o Compact Flash option
- o Lockable front panel for security
- o 15" Thin Bezel Resistive Touch Monitor
- o 3 Year Warranty



# Specifications:

## 15" All-in-One Semi-Integrated Solution



### MODEL

### All in One DigiPoS IT 1500 PoS System

<b>CPU</b>	<b>CELERON/PENTIUM</b>	<b>PENTIUM M</b>
	Celeron 2.0GHz (FSB400) or	Pentium M 1.6GHz (FSB533) Pentium M 1.86GHz (FSB533)
<b>DISPLAY MODULE</b>	15" color TFT, 1024 x 768, 250 nits	
<b>CHIPSET</b>	Intel 852GM/ICH4	
<b>DISPLAY</b>	4X AGP LCD/VGA controller, advanced hardware 2D/3D GUI engine Sharing memory architecture up to 64MB	
<b>SYSTEM MEMORY</b>	1 x 184 pin supporting DDR up to 1GB	
<b>L2 CACHE</b>	CPU built-in	
<b>AUDIO</b>	MIC-in, Speaker-out (front access)	
<b>SPEAKERS</b>	Internal speakers x 2	
<b>DRIVE BAY</b>	3.5" HDD x 1	
	Slim CD-ROM or equivalent device x 1	
	Compact Flash slot x 1 (optional)	
<b>ETHERNET</b>	100/10 Base-T PnP Ethernet with RJ-45 phone jack Support WAKE-ON-LAN	
<b>PANEL PC I/O</b> (accessible inside of kiosk cabinet)	Serial Ports x 4, COM 1,2 & 4 with +5V/12V power output on pin 9, COM 3 is internal type reserved for touch screen, optional COM 5 Parallel Port x 1: supports SPP/EPP/ECP PS/2 Mouse Interface x 1 PS/2 Keyboard Interface x 1 USB 2.0 x 4 (2 front & 2 rear access) VGA Interface x 1 Cash Drawer RJ-11 with 12V power output	
<b>POWER SUPPLY</b>	ATX 120W, input range: 100~240V	
<b>TOUCHSCREEN</b>	15.0" resistive type with RS-232 controller	
<b>DIMENSION</b>	379 x 312 x 358 mm (w/o 2nd display)	
	379 x 312 x 408 mm (with 2nd display)	
<b>PERIPHERAL DEVICES</b> (optional)	Slim type CD-ROM MSR: Magnetic card reader, swipe type, track I, II & III, KB wedge Customer Display (VFD): 20*2 lines RS-232 interface Customer Display (VFD) w pole: 20*2 lines RS-232 interface 2nd display: 10.4" LCD monitor Dallas i-Button w receptacle and magnetic key CF socket: CF function COM5: USB to COM5	
<b>STAND</b>	Tilt angle: 15°~75° front/back, swivels left/right	