



## 15A2 15" LCD All-in-One Touchcomputer

### Provides Versatility for POS Applications

**The Elo 15A2 15" LCD all-in-one touchcomputer** is an attractive solution for POS applications. Its optional peripherals can easily be integrated into the 15A2's compact design. A choice of optional peripherals can be installed including: a magnetic stripe reader, vacuum fluorescent, rear-facing LED customer display, biometric fingerprint recognition device, and speaker bar with/without a built-in single or omni-directional barcode scanner. Its 1024 x 768 resolution with a 5:4 ratio displays clear, precise graphics and a contrast ratio of 500:1 together with a typical LCD panel brightness of 300 nits provides bright, high contrast for improved readability.

#### Features

- Space-saving, integrated, all-in-one touchcomputer with the footprint of a standard 15" LCD display
- Silent, fanless Intel® Celeron® M design is well suited for point-of-sale, kiosks and POI applications
- Industry standard VESA mounting options, configurable as both a desktop or wall-mount
- Choice of Microsoft Windows Embedded for POS (WEPOS), XP Professional or Vista
- Available as an embedded system or with an integrated hard drive
- Full range of "field" replaceable and serviceable point-of-service options such as an integrated MSR, rear-facing customer display or barcode scanner
- Available with Acoustic Pulse Recognition (APR), AccuTouch five-wire resistive, IntelliTouch surface acoustic wave or CarrollTouch infrared touch technologies
- "Designed for touch" for public access with cables hidden from user's view; controls on the side rather than the front, plus lockout function to minimize public tampering
- Integrated (optional) wireless LAN for expanded access and advanced media applications
- Two serial, four USB 2.0 and Ethernet ports for maximum expansion
- Worldwide agency approvals

# 15A2 15" All-in-One Touchcomputer Specifications

## Touchcomputer

Processor	Intel Celeron M 1GHz CPU
Memory (RAM)	1GB DDR2 standard on 1 of 2 slots (expandable to 2GB max)
Chipset	Intel 915GME/ICH6
Video	Intel GMA 900 up to 128MB shared w/ DVMT
BIOS	ACPI 2.0, APM 1.2, SMBIOS 2.4, PXE, WOL, WFM 2.0
Optional Operating System	Microsoft® Windows® XP Professional Service Pack 2 Microsoft® Windows Embedded for Point of Service (WEPOS) Microsoft® Vista
Serial Ports	2 x RS232 serial (RJ45, 8 position); COM2 is RS232, RS422 and RS485 selectable
USB Ports	4 x USB self powered 2.0; 1 port is 12V powered USB (1.5A) for POS peripherals
VGA port	1 x VGA D-SUB
Ethernet 100/10Base-T Port	1 x LAN RJ45
Cash Drawer/Modem Port	BIOS selectable; 1 x cash drawer (RJ11, 6 position) or 1 x RJ11 port for optional internal modem
PS/2 port	1 x PS/2 Universal (default to keyboard compatibility)
Audio port	1 x 3.5mm audio-out; 1 x 3.5mm mic-in
Hard Disk Drive	1 x 2.5" SATA hard drive
Compact Flash slot	1 x Compact Flash type I
MiniPCI slot	1 x MiniPCI type III A/B
Real Time Clock	Replaceable Lithium battery backed up real time clock
Languages	Win XP (33 language groups); WEPOS (5 language groups)

## Touchmonitor

Case/Bezel color	Dark Gray
Display	Size: 15.0 in. diagonal; Type: active matrix TFT LCD; aspect ratio: 4:3
Touchscreens	AccuTouch five-wire resistive, APR Acoustic Pulse Recognition, CarrollTouch infrared, IntelliTouch surface acoustic wave
Useful screen area	Horizontal: 304.1 mm (11.98in.); vertical: 228.1 mm (8.99 in.)
Maximum dimensions* (with stand)	Width: 357.7 mm (14.09 in.); height: 338.5 mm (13.37 in.); depth: 237.6 mm (9.36 in.)
Optimal (native) resolution	1024 x 768
Colors	16.7 million
Brightness (Typical)	No touchscreen: 250 cd/m <sup>2</sup> ; AccuTouch: 200 cd/m <sup>2</sup> ; APR: 230 cd/m <sup>2</sup> ; CarrollTouch: 230 cd/m <sup>2</sup> ; IntelliTouch: 230 cd/m <sup>2</sup>
Response Time	Trise: 2 msec; Tfall: 6 msec
Viewing Angle (typical from center)	Horizontal (left/right): 60° looking left at a CR=10; 65° looking right at a CR=10; Vertical (up/down): 70° looking up at a CR=10; 70° looking down at a CR=10
Contrast Ratio (typical)	500:1
Temperature	Operating 0°C to 35°C; Storage -20°C to 60°C
Humidity (non-condensing)	Operating 20% to 80%; Storage 5% to 95%
Weight (with all options)	Actual 8.8 kg (19.4 lbs); shipping 11.6 kg (25.5 lbs)
Agency approvals	UL/cUL(*Recognized component), FCC, CE, VCCI, Ctick, EN60950
Backlight Lamp Time to 1/2 Brightness (typical)	40,000 hours
MTBF (mean time between failures)	50,000 hours demonstrated
Warranty	3 years
Other Features	75mm VESA mounting; accessible HDD, compact flash, MiniPCI card; removable base; threaded holes on base bottom for tabletop mounting; 2 watt/channel speakers located in display head; touchscreen sealed to bezel; touchscreen sealed to LCD
Optional Peripherals	Magnetic stripe reader, serial customer display (20x2 VFD), biometric fingerprint reader, speaker bar, barcode scanner, wireless card, (modem daughter card, TV-tuner available)
Lockable OSD Controls	Volume, brightness, sharpness, contrast, color temperature, OSD position and orientation, OSD language (English, French, Italian, German, Spanish), factory reset, power button

\*Dimensions vary with stand position and options selected



To find out more about our extensive range of Elo touch solutions, go to [www.elotouch.com](http://www.elotouch.com), or call the office nearest you.

### North America

Elo TouchSystems  
301 Constitution Drive  
Menlo Park, CA 94025-1110

800-ELO-TOUCH

Tel 1-650-361-4800

Fax 1-650-361-4722

[customerservice@elotouch.com](mailto:customerservice@elotouch.com)

### Europe

Tel +32 (0)16 35 21 00

Fax +32 (0)16 35 21 01

[elosales@elotouch.com](mailto:elosales@elotouch.com)

### Asia-Pacific

Tel +81 (45) 478-2161

Fax +81 (45) 478-2180

[www.tps.co.jp](http://www.tps.co.jp)

### Latin America

Tel 786-923-0251

Fax 305-931-0124

[www.elotouch.com.ar](http://www.elotouch.com.ar)



Tyco Electronics Corporation and its Affiliates in the TE Touch Solutions business unit of the TE Connectivity Ltd. family of companies (collectively "TE") reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

AccuTouch, CarrollTouch, Elo (logo), Elo TouchSystems, IntelliTouch, TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks of the TE Connectivity Ltd. family of companies. Windows is a trademark of Microsoft Corporation.

Copyright 2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company. All rights reserved. 04/11

