

PARTNER

CARE . TRUST . RESPONSIBILITY

PT-6200 & PT-6212 Key Features

- Fanless design
- 10.4" Touch screen (PT-6200)
- 12.1" Touch screen (PT-6212)
- Integrated MSR, Thermal Printer, & Customer display
- Modular design



PT-6200 & PT-6212
Revolutionary
all-in-one POS solution

Partner Tech UK Corporation
www.partnertech-uk.com

PT-6200 & PT-6212: Revolutionary all-in-one POS solution

The compact, space saving design is ideally suited to many an application.

Boasting either a 10.4" (PT-6200) or 12.1" (PT-6212) touch screen the terminal also has an integrated 80mm thermal printer, 3 track magnetic card reader and 2 x 20 VFD display. With multiple connections these products will link seamlessly with existing systems. Thanks to their small footprint and spill-proof design they can be used in both hospitality and retail.

The modular design also makes them easy to install and maintain.



Magnetic Swipe Reader



Rear VFD Customer Display



80mm Thermal receipt printer with Auto cut and Paper Feed



Modular Design for easy maintenance

| | PT-6200 | PT-6212 |
|------------------------|--|--|
| Processor | Intel Celeron-M Processor @ 600MHz | Intel Celeron-M Processor @ 1GHz |
| Memory | 512MB | 1G |
| Display | 10.4" TFT-LCD | 12.1" TFT-LCD |
| Resolution | 800 x 600 | 1024 x 768 |
| Touch Screen | 5-wire Resistive touch | 5-wire Resistive touch |
| LCD brightness | 250 nit (w/o touch) | 250 nit (w/o touch) |
| Network | 10/100/1000Mbps onboard Ethernet controller | 10/100/1000Mbps onboard Ethernet controller |
| Storage | SATA 3.5" 80GB hard drive | SATA 3.5" 80GB hard drive |
| I/O Interface | 4 COM ports 1 RJ11 port (+24V) 1 PS2 Keyboard port 1 RJ-45 LAN port 4 USB ports 1 DC +12V | 4 COM ports 1 RJ11 port (+24V) 1 PS2 Keyboard port 1 RJ-45 LAN port 4 USB ports 1 DC +12V 1 VGA port |
| Operating System | WEPOS/POSReady/Windows 2000/CE. Net/Linux | WEPOS/POSReady/Windows 2000/CE. Net/Linux |
| Power Supply | AC 100V~240V/DC12V/12.5A 150 watt power adaptor | AC 100V~240V/DC12V/12.5A 150 watt power adaptor |
| Temperature | Operating Temperature: 0~40 degree C Storage Temperature: -20~60 degree C | Operating Temperature: 0~40 degree C Storage Temperature: -20~60 degree C |
| Humidity | Operating Humidity:15% ~ 80% Storage Humidity:15% ~ 80% | Operating Humidity:15% ~ 80% Storage Humidity:15% ~ 80% |
| Dimension | Physical:328mm (W) x 289.3mm (D) x 246.8mm (H) | Physical:328mm (W) x 289.3mm (D) x 246.8mm (H) |
| Integrated Peripherals | Triple track magnetic card reader Customer display module 80mm Thermal receipt printer | Triple track magnetic card reader Customer display module 80mm Thermal receipt printer |
| Colour | White or Dark Charcoal | White or Dark Charcoal |
| Option | 4G USSD | 4G USSD, RFID, WLAN |



Partner Tech Corporation

UK
T: +44 (0) 1928 579 707
F: +44 (0) 1928 571 308
E: sales@partnertech-uk.com

Taiwan
T: +886 2 291 88500
F: +886 2 291 53405
E: sales@partner.com.tw

USA
T: +1 949 598 1888
F: +1 949 598 0088
E: sales@partnertechcorp.com

Europe
T: +49 (0)40 450 635 0
F: +49 (0)40 450 635 130
E: info@partner-tech.eu

China
T: +86 21 676 9 6667
F: +86 21 676 9 669
E: sales@partnertech.com.cn