



KEY FEATURES

- Intel VIA® C7 2.0GHz w/ 128KB L2 Cache
- Microsoft® Windows XP or POS Ready
- 160GB SATA HDD
- 1GB DDR2 memory
- Durable 15" touch screen
- Energy efficient fan-free design
- Advance exchange (optional)
- Onsite Service (optional)
- Private label front bezel logo (option)

KS6215 Series

Posiflex Fan-Free KS6215 Series

The KS6215 is our fan-free, high performance POS terminal that is available at a very attractive price point that you will love. Not a limited offer, the KS6215 is a standard product featuring our patented aluminum chassis for maximum heat dissipation, a 2.0GHz CPU, Microsoft Windows XP or POS Ready or our special value bundle with Windows Embedded for Point of Service and a 2-track MSR. Available in a desktop configuration which easily converts to a wall mount solution. The KS6215 is ideally suited to end users looking for value and an attractive price with no compromise on quality. Call today and find out how the KS6215 can boost your sales and help GROW your bottom line.

For more information call 888.968.1668 today!

Specifications

| Function | KS6215 |
|-------------------------------|--|
| Processor | VIA C7 2.0GHz |
| Memory | Standard 1GB, DDR2 SDRAM SO-DIMM x 1 |
| VGA Memory | 16MB - 64MB (shared) |
| Power Supply | 12V DC power adaptor, 80W |
| Housing | Aluminum die casting |
| Speaker | Built-in |
| OS Support | Microsoft® Win XP Pro / POS Ready / WEPOS |
| Safety Certifications | FCC-A, CE-A, RoHS WEEE |
| Display | |
| LCD | 15" LCD, 200nits, 1024 x 768 XGA |
| Touch Sensor | Resistive |
| Touch Controller | USB interface mouse emulation |
| Tilt Adjustment | From 17.5° to 76.5° |
| Expansion | |
| Storage Device | 160GB SATA HDD |
| Mounting Option | Desktop or wall mount (wall mount bracket sold separately) |
| Connectivity | |
| Audio Port | 2 Watt audio output built-in |
| LAN Port | 1 x 10/100 Base T Ethernet |
| Parallel Port | 1 x SPP / EPP / ECP |
| Serial Port | 2 x DB9, each with +5V |
| UPS Port | N/A |
| USB Port | 4 x USB 2.0 + 1 proprietary port for SD-402 |
| PS/2 Mouse Port | N/A |
| KB Port | N/A |
| CR Port | 1 x, for single cash drawer, 12V DC |
| Environment | |
| Operation Condition | 0°C ~ +40°C (32°F ~ +104°F), 20% RH ~ 80%RH, non-condensing max, wet bulb 26°C (78.8°F) |
| Storage Condition | 20°C ~ +60°C (-4°F ~ +140°F), 10°C ~ 80°C non-condensing max, wet bulb 28.9°C (84.0°F) |
| Options | |
| 2nd LCD Display | LM6101B |
| Customer Display | PD2501: 11mm, 2x20 VFD display, 5x7 dot matrix, RS232 interface PD2602: 9mm, 2x20 VDF display, 5x7 dot matrix, RS232 or USB interface PD305: 9mm, 2x20 LCD display, 5x7 dot matrix, RS232 or USB interface PD2604U00EFP: 2x20 VFD display, 9mm characters, USB (Rear Monitor Mount) PD3100X00EEP: 2x20 LCD display, 9mm characters, USB (Rear Monitor Mount) |
| SD-402 Magnetic Stripe Reader | Optional 2-track or 3-track MSR with/without Finger Print Sensor |

KS6215 Main Board Interface Diagram



Customer Displays



About Posiflex

Posiflex has four primary objectives - provide revolutionary technology, reliable quality, reasonable pricing and recognized service. As a 25 year design and manufacturer of Point-of-Service (POS) and industrial touch terminals, Posiflex has over 30 patents awarded for innovative design as a POS pioneer, and leader. In partnership with software application companies, Posiflex's products are sold worldwide through VARS and distributors to various vertical industries. Posiflex's comprehensive suite comprises of a wide range of peripherals, terminals ranging from small footprint electronic cash register replacements, to POS terminals, to robust back office file servers in our two ISO 9001/9002/ 14001 certified facilities.

POSIFLEX™

Be the Pioneer, Be the Leader
30689 Huntwood Avenue

Hayward, CA 94544

Toll-free: 888.968.1668

Phone: 510.429.7097

Fax: 510.475.0982

E-mail: sales@posiflexusa.com