Printer

TRST-A00

- Cost Efficient
- Environmental Friendly - Energy Saving Mode
- Easy to Maintain - PC-less Setting

Black Model

White Model

General Specifications	
Model	TRST-A00 Single-sided
Print Method	Direct thermal Two color printing
Print Speed	Max. 170 mm/s
Paper Width	80 mm (72 mm printable) 58 mm (54 mm printable)
Roll Diameter	Max. 80 mm
Resolution	203.2 × 203.2 dpi (8 dots/mm)
Font Type 2	13 × 28 dots (Standard) 10 × 28 dots (Compressed)
Printable Area	80 mm:42 char (Standard), 56 char (Compressed) graphics max. 560 dots wide 58 mm:32 char (Standard), 42 char (Compressed) graphics max. 424 dots wide
Character Sets	PC437, PC850, PC852, PC857, PC858, PC860, PC863, PC865, PC866, PC949, PC1252, PC1253, PC1254
Barcodes	UPC-A, UPC-E, JAN13 (EAN), JAN8 (EAN), Code 39, Code 128, Interleaved 2 of 5, PDF417, Code93, CODABAR (NW-7)
Interfaces	USB 2.0 or RS-232C POS drawer and power supply I/F
Power Consumption	Fast mode:75 W max. Energy saving mode:55 W max.
Reliability	MCBF:52 million lines per thermal head Auto Cutter : 1 million cuts
Other Features	Drop-in paper loading; Paper exhaust/near end sensor and indicator(Limit is adjustable by user);Partial cut autocutter; 58 mm paper guide;Cover release system
Cabinet Color	CB (Black), FW2 (White)
Operating Temperature	5 to 50℃
Dimensions	145.5 (W) × 185.5 (D) × 141 (H) mm 5.72"(W) × 7.3"(D) × 5.55"(H)
Weight	1.4 kg/ 3.09 lbs
Options	58mm paper partition, Water-proof cover, AC Adapter, Y/I cable for power supply