



www.toshibatec-eu.com

The ST-70 has been designed for the hostile hospitality and retail markets. There is no need for any cooling fans. This provides silent operation so the only sound to be heard is the sound of the customers. Combine this with Toshiba TEC's legendary build quality and knowledge of the market place and the result is an ideal POS device for any environment.

Leading the way through Quality and Innovation



ST-70

Specifications

CPU	Ultra low voltage, Celeron Fan-less CPU
RAM	256 MB on board (expandable to 512 MB)
Cache Memory	256 KB on die
Compact Flash	Option
HDD	2.5" IDE (option), max. 2 drives
FDD	External FDD (option)
PCMCIA	Option
Interfaces	Serial x 4 (2 powered, 2 non-powered), Parallel, USB x 3 (2.0), POS keyboard, Mouse, Drawer x 2, LAN (10BASE-T/100BASE-TX)
OS Support	Windows 2000/XP
Operator Display	12.1" colour TFT with touch panel
Customer Display	2 lines x 20 characters VFD (option)
Magnetic Card Reader	Option
Power	External AC adapter (allowing very small PoS footprint)
UPS	Option
Dimensions	296 (W) x 278 (D) x 283.7 - 307.6 (H) mm (without MCR)
Weight	7.1 kg (including options)
Operating Temperature	5 - 35° C

High reliability

The touch screen and front panel are sealed together for a spill-proof design. The machine does not need vent holes, therefore, no dirt or undesirable foreign objects can enter it. The ST-70 stays clean inside, providing even better reliability.

Operating System Support:

- Windows 2000®
- Windows XP®

Your TOSHIBA TEC dealer:

All company and/or product names are trademarks and/or registered trademarks of their respective owner's. All features and specifications described on this brochure are subjected to change without notice.

Fast interfacing

The USB 2.0 interfaces have a maximum transmission speed of 480 Mbps, which allows the connection of peripherals that require high-speed transmission. The optional PCMCIA card bus is a fast, 32-bit bus.

Easy maintenance

The hard disk is accessible by the side cover. Replacement takes only seconds. The external interfaces are located at the front of the machine, which makes it easy to connect and disconnect peripherals.

More improvements

The new super bright TFT screen with its wider viewing angle makes operation quicker and more comfortable. Also, there is increased functionality with the introduction of two powered serial ports. This means that peripherals are less susceptible to misuse or failure.

TOSHIBA

TOSHIBA TEC EUROPE RETAIL INFORMATION SYSTEMS

Austria
Handelskai 388/Top 621
Donau Business Center
AT - 1020 WIEN
T. +43 (0)1 319 72 11
F. +43 (0)1 319 67 70
info@toshibatec-eu.de

Belgium & Headquarters
Rue de la Célidée, 33 - Celideestraat 33
BE - 1080 BRUXELLES/BRUSSEL
T. +32 (0)2 410 21 00
F. +32 (0)2 410 68 69
F. HQ: +32 (0)2 410 79 87
info@toshibatec-eu.be

France
23/25 Avenue Jeanne d'Arc
FR - 94117 ARCUEIL Cedex
T. +33 (0)1 58 07 20 00
F. +33 (0)1 58 07 20 01
info@toshibatec-eu.fr

Germany
Europark Fichtenhain B15
DE - 47807 KREFELD
T. +49 (0)2151 838 01
F. +49 (0)2151 838 480
info@toshibatec-eu.de

Ireland
Unit 7, Crumlin Business Centre
Stannaway drive
IE - DUBLIN 12
T. +353 (0)1 465 22 20
F. +353 (0)1 465 22 29
info@toshibatec-eu.ie

Portugal
Taguspark - Parque de Ciência e Tecnologia
Nucleo Central - Sala 268
PT - 2780-920 OEIRAS (Lisboa)
T. + 351 21 422 20 64
F. + 351 21 424 02 11
comercial@toshibatec-eu.pt

Spain
C/Doctor Esquerdo 207
ES - 28007 MADRID
T. +34 91 502 15 90
F. +34 91 501 81 00
retail@toshibatec-eu.es

UK
Campus 300, Spring Way
Maylands Avenue, Hemel Hempstead
GB - HERTFORDSHIRE, HP2 7GG
T. +44 (0)870 890 7200
F. +44 (0)870 890 7350
marketing@toshibatec-eu.co.uk

GROUP Companies

**TOSHIBA TEC NETHERLANDS
RETAIL INFORMATION SYSTEMS B.V.**
Postbus 2510, NL - 3800 GB AMERSFOORT
Softwareweg 3, NL - 3821 BN AMERSFOORT
T. +31 (0)33 453 81 00
F. +31 (0)33 455 44 11
info@toshibatec-eu.nl

TEC Polska Sp. z o.o.
ul. Marynarska 21
PL - 02-674 WARSZAWA
T. +48 (0)22 640 48 58
F. +48 (0)22 640 48 53
info@tec.pl