

POS-3000

Next Generation POS System

The glossy POS-3000 System is an epochal POS terminal that fulfills both your visual and functional demands. This much anticipated all-in-one POS system features sleek and stylish exterior with piano gloss finish, giving your counter a refreshing and elegant look. Its compact footprint saves valuable counter space and is ideal for situations where a space is an issue. The touch screen monitor can be tilted from 5 to 90 degree, ensuring easy interactivity for users and delivers accurate input.

POS-3000 series comes with rich I/O ports (including 8 USB 2.0 and 3 Serial ports), which allow the users to have more flexibility to integrate their own peripherals with the terminal. It is also equipped with smart fan function, which automatically adjusts the fan speed of the processor depending on the temperature of the latter.



Feature



Integrated Stylish Peripherals



Excellent connection and interface variety

Core 2 Duo
T7400

15" LCD
1024 x 768

Low-Noise
System

USB 2.0

Water-Spill
Proof

Internal
Adapter

- Multiple Colors Available (Red /White/Black)
- Variety of CPU Selectable For Cost-Effective Solutions (Atom N270 to Core 2 Dual T7400)
- High Capacity Ram Expandable (Up To 4 GB)
- Low Noise System with Smart Fan to Ensure Quiet and Steady Operation
- Dual Gigabit LAN Ports
- Excellent Connectivity (6 USB 2.0 External)
- Water Spill Proof
- Internal Cable Routing Base Design Ideal for Small Workplace Operation
- Optional MSR/Customer Display/2nd VGA Displays
- Internal Power Adapter

POS-3000

Next Generation POS System

Specification

Series	Zenis (POS-3000 Series)	
Model	POS-3000 AT	POS-3000 CD
Main Board		
CPU	Intel Atom N270 (1.6GHz , 512KB Cache, 533MHz FSB)	Intel Core 2 Duo T7400 (2.16GHz, 4M Cache, 667M FSB) Intel Core Duo T2500 (2GHz , 2M Cache , 667M FSB) Intel Celeron M 440 (1.86GHz, 1M Cache, 533M FSB)
Chipset	Intel 82945GME + 82801GBM(ICH8)	
System Memory	2 x 200pin DDR2 533/667MHz SODIMM Socket , up to 4GB	
Graphic Memory	Share System Memory 64~224MB	
OS Support	POS Ready, XP Pro, Vista, Linux	
Display		
Screen Size	15"	
Brightness	250 nits	
Resolution	1024 x 768 Pixel	
Touch Screen	5 Wire Resistive Type or SAW	
Tilting Angle	15~90 Degrees	
Storage		
HDD	1x 2.5" SATA	
Compact Flash	1 x Slot Type I II,Non-removable	
I/O Ports		
Serial	3 x COM with Power Selected 5/12V on pin9	
Parallel	1 x DB25 Parallel Port	
USB	6 x USB 2.0 (External), 2 x USB 2.0 (Internal, 1 reserved for touch screen)	
PS/2 Mouse	1 x 6-pin Mini DIN	
PS/2 Key Board	1 x 6-pin Mini DIN	
Programmable KB	Optional	
LAN	2 x RJ-45, Giga LAN Support	
VGA	1 x DB-15, Female	
DC Out	1 x 12VDC Jack for Customer Display or 2nd Display	
Cash Drawer	1 x RJ-11, 12/24 VDC Selectable	
Audio Jack	1 x Line Out, 1 x MIC In, 2 x Internal Speaker 2W	
Others		
Power Input	Internal Adapter 12VDC/90W, 4-pin Connector with Lock	
Color	White, Black, Red	
Compliance	FCC / CE / WEEE / RoHS	
Weight	7.3 Kg	
Dimension(WxDxH:mm)	385 x 360 x 245	
Operating Temperature	0°C~40°C	
Operating Humidity	20% ~ 80% RH, non-condensing	
Storage Temperature	-20°C~ 60°C	
Storage Humidity	20% ~ 85% RH, non-condensing	

Optional Accessories



PRP-250 Receipt Printer



Durable Cash Drawers



VFD-890 Customer Display



Beyond Mere POS

<http://www.fametech.com.tw>

